

2204C Coagulation Analyzer



Features

- 1- 4 channels (4 durable LED detectors for 4 different parameters analysis)
- 2- Easy Windows operation system with touch screen or mouse, large LCD display
- 3- Advanced scattered light principle and percentage analysis ensure accurate results
- 4- Low reagent consumption
- 5- Large memory, up to 10,000 results can be stored
- 6- QC and calibration program incorporated
- 7- Multiform result output including patient comprehensive report
- 8- Easy software upgrade by SD card, support USB mouse and keyboard
- 9- Auto self-check when power on
- 10- Electronically-linked pipette

System Specifications

Analysis Parameters	PT, APTT, TT, FIB, F2, F5, F7, F8, F9, F10, F11, F12, Heparin, APC-R, Protein S, Protein C
Principle	Scattered light with percentage analysis
Sample Volume Required	PT: 25ul
	APTT: 25ul
	TT: 25ul
	FIB: 25ul
Testing Channel	4 Channels
Light Source	Durable LED detector
Sample Position	24 positions
Reagent Position	6 positions (1 magnetic mixer included)
Testing Time	Normally 20-60 secs, Maximum time up to 600 secs
Minimum Reagent Consumption	25µL for TT, FIB, PT, APTT
Position Warming-up	37°C(±0.5°C)
Memory	10,000 test results
Display	6" LCD display
Interface	RS-232, USB, SD card interface
Input	Touch panel or USB mouse
Output	External printer (optional)
Power supply	AC 110-220V±10%, 50-60Hz
Net Weight	8KG
Dimension L×W×H(mm)	410×310×160

Hiperion



Medizintechnik GmbH & Co.KG
Carl-Zeiss-Str.18 D-6332 Roedermark,Germany